



## Product Snapshot

<b>Applications</b>	Pre-terminated FTTx Drop Cable Aerial Self-Support, Direct Buried, Duct
<b>Connector Types</b>	SC, LC, FC, ST (APC angled polish or UPC) Ruggedized Connector (Outside Plant hardened SC/APC)
<b>Cable Types</b>	ezDROP   Flat (Dielectric or Toneable)
<b>Fiber Count</b>	1 fiber Terminated (standard) Spare fibers available (on request)
<b>Fiber Types</b>	BendBright® Singlemode Fiber (standard) BendBright-XS Singlemode Fiber (on request)
<b>Options</b>	Pre-terminated ends: 1 (pigtail) or 2 (jumper) Packaging: coils (up to 300') or reels Cordage: 2.0mm or 3.0mm (for standard connectors)
<b>Performance</b>	ANSI/ICEA, RDUP/RUS, Telcordia GR-20 Drop cable specifications

## The quickest way to install a fiber drop cable.

FiberSource pre-terminated OSP drop cables provide easy FTTx (Fiber -To -The x) installation and termination using existing hardware and installation methods for drops to homes and businesses. Its flat profile is compatible with existing wedge (P) clamps. An all-dielectric version eliminates the need for bonding or grounding. A toneable version adds a 24 AWG conductor that provides underground location capability.

FiberSource preinstalled connectors provide for quick subscriber connections. The drop cable assemblies are precision manufactured to rigorous quality standards, assure reliable performance and compatibility. Tight tolerance control results in reliable low-loss connections and reconnections over the long term.


The Ruggedized Connector, an outside plant hardened SC/APC, is compatible with industry standard OSP terminals.

FiberSource preinstalled standard connectors allow for easy and effective routing and termination in Ftx equipment - available in SC, LC, FC, & ST connectors with either APC (angled) or UPC (ultra) polish performance. Each pre-terminated cable is made to selected lengths with your choice of connectors and 2.0mm or 3.0mm OD furcated legs.

## OSP DROP | Pre-terminated



Ruggedized Connector  
(OSP hardened SC/APC)



SC | UPC Connector

\*Call your FiberSource Representative for cable type and availability. Some variations may have limited availability or may be subject to minimum order quantity requirements.



## Features & Benefits

### Simple Patching Connectivity

- [+] Available with industry standard connectors or ruggedized connector (outside plant hardened) [ + ] Eliminate field splicing
- [+] Connectors compatible with industry standard receptacles.

### Fiber Options

- [+] BendBright bend-tolerant singlemode fiber (standard)
- [+] BendBright-XS bend-insensitive fiber (on request)

### Multi-purpose Installation & Use

- [+] Suitable for self-support aerial, duct, & buried direct
- [+] Coil & spool packaging

### Reliable Lifetime Performance


- [+] Exclusive ColorLock fiber coating for permanent embedded color and long-term performance
- [+] Standards-based connector & cable performance

### Package Options

- [+] Coils: 50 to 300 feet (50 foot increments)
- Reels: >300 feet (50 foot increments)
- [+] Individually wrapped

## Ordering Guide

For Ordering or More Information Contact us at [sales@fibersource.net](mailto:sales@fibersource.net) or 888.342.3776.



\*Manufactured under license from Corning Cable Systems

\*Call your FiberSource Representative for cable type and availability. Some variations may have limited availability or may be subject to minimum order quantity requirements.