



Features:

- Based on IEC 61754-20: LC Type Connector
- FOCIS 10a Compliant
- Meets UL94-VO Flammability Requirements
- Telcordia GR-326-CORE Tested
- Ferrule ID: 125.5 μ m (Standard) 125 μ m and 126 μ m Special Order
- Insertion Loss: \leq 0.25dB
- Return Loss: \geq 55dB
- Operational Temperature: -40°C~+85°C
- Temperature Stability: \leq 0.3dB(-40°C~+85°C)
- Mating Durability: \leq 0.2dB(500 times)
- Housing Color: Blue
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS01124 LC SM OTW Simplex for 1.6/2.0mm Cable
FS01126 LC SM OTW Simplex for 3.0mm Cable
FS00922 LC SM OTW Simplex with Short Boot



Features:

- Based on IEC 61754-20: LC Type Connector
- Ferrule ID: 127 μ m
- Meets UL94-VO Flammability Requirements
- Fiber Types: 50/125 or 62.5/125
- Insertion Loss: ≤ 0.4 dB (MM)
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤ 0.3 dB(-40°C~+85°C)
- Mating Durability: ≤ 0.4 dB(500 times)
- Housing Color: Beige
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS01125 LC MM OTW Simplex for 1.6/2.0mm Cable
FS01127 LC MM OTW Simplex for 3.0mm Cable
FS00821 LC MM OTW Simplex with Short Boot



Features:

- Based on IEC 61754-20: LC Type Connector
- FOCIS 10a Compliant
- Meets UL94-VO Flammability Requirements
- Telcordia GR-326-CORE Tested
- Ferrule ID: 125.5 μ m (Standard) 125 μ m and 126 μ m Special Order
- Insertion Loss: ≤ 0.25 dB
- Return Loss: ≥ 55 dB
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤ 0.3 dB(-40°C~+85°C)
- Mating Durability: ≤ 0.2 dB(500 times)
- Housing Color: Blue
- 19mm Short Boot
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS00922 LC SM OTW Simplex with Short Boot



Features:

- Based on IEC 61754-20: LC Type Connector
- Ferrule ID: 127 μ m
- Meets UL94-VO Flammability Requirements
- Fiber Types: 50/125 or 62.5/125
- Insertion Loss: ≤ 0.4 dB (MM)
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤ 0.3 dB(-40°C~+85°C)
- Mating Durability: ≤ 0.4 dB(500 times)
- Housing Color: Beige
- 19mm Short Boot
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS00821 LC MM OTW Simplex 1.6/2.0mm with Short Boot



Features:

- Based on IEC 61754-20: LC Type Connector
- FOCIS 10a Compliant
- Telcordia GR-326-CORE Tested
- Ferrule ID: 125.5 μ m
- Insertion Loss: ≤ 0.25 dB (SM)
- Return Loss: ≥ 55 dB(SM)
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤ 0.3 dB(-40°C~+85°C)
- Mating Durability: ≤ 0.2 dB(500 times)
- Housing Color: Blue
- Removable Duplex Clip
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS01128 LC MM OTW Duplex for 1.6/2.0mm Cable
FS01128-30 For 3.0mm Cable



Features:

- Based on IEC 61754-20: LC Type Connector
- Ferrule ID: 127 μ m
- Fiber Types: 50/125 or 62.5/125
- Insertion Loss: ≤ 0.4 dB (MM)
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤ 0.3 dB(-40°C~+85°C)
- Mating Durability: ≤ 0.4 dB(500 times)
- Housing Color: Beige
- Removable Duplex Clip
- Over Molded Dust Cap
- Made in the U.S.A.

Part Numbers: FS01129 LC MM OTW Duplex for 1.6/2.0mm Cable
FS01129-30 For 3.0mm Cable



Features:

- Based on IEC 61754-20: LC Type Connector
- FOCIS 10a Compliant
- Meets UL94-VO Flammability Requirements
- Telcordia GR-326-CORE Tested
- Ferrule ID: 125.5 μ m (Standard) 125 μ m and 126 μ m Special Order
- Insertion Loss: ≤ 0.30 dB
- Return Loss: ≥ 65 dB
- Operational Temperature: -40°C~+85°C
- Temperature Stability: ≤ 0.3 dB(-40°C~+85°C)
- Mating Durability: ≤ 0.2 dB(500 times)
- Housing Color: Green
- Over Molded Dust Cap
- Made in the U.S.A.

Part Number: FS01123 LC APC OTW Simplex for 1.6/2.0mm Cable
FS01122 LC APC BTW 900um Cable