

# Universal Split Base HDPE CVK101035A

UNIVERSAL SPLIT  
BASE HDPE  
CVK101035A

The CVK101035A Universal Split Base HDPE Pedestal is a ground, wall, pole, or pad mountable pedestal that can be used for a variety of applications to splice, patch, drop, express optical fiber or coax drops to subscribers. It can also be used to house a terminal or closure. A wide selection of accessories and accessory kits are available for factory or onsite customization.

These pedestals can provide most of industry standard or common connector types including:

- Corning Optitap® and Evolv PushLok®
- Commscope DLX®
- Standard SC and LC

These pedestals can also be equipped with up to six (6) splice trays for 12, 24 and 48 fibers including ribbon fiber. When specified, we can include trays that will accommodate splitters as well.



Model CVK101035A Universal Split Base Pedestal

Call your FiberSource Representative for type availability. Some variations may have limited availability or may be subject to minimum order.

## FEATURES

- Accommodates up to 288 single-spliced fibers or 432 ribbon spliced fibers.
- Technicians have ample 360-degree access to splicing and connection areas.
- Designed and tested in accordance with Telcordia GR-13-CORE.
- Two-piece split base allows contractors to place the pedestal over conduit fed cable loops and can be used to refurbish damaged pedestals.
- Provides adequate protection for splices and connectors without need for any extra components, i.e. "box-in-a-box."
- Compatible with all existing cable plants.
- Ground/mount stake is included standard.
- Cap attaches to the base using a self-actuating lock using a Bellcore 216 Hex Lock Can Wrench. Other lock types are available.
- Internal tunnel accessible from outer side allows placement of drops without disturbing internal soil and gravel.
- UV stable and impact resistant HDPE outer housing
- Accepts most splice trays.
- A wide variety of accessories are available for splicing, grounding, and patching.
- All stainless-steel hardware
- Frame with accessories can be mounted in rear or center position.
- Entire frame can be removed for splicing.

Optitap® and Evolv Pushlok® are registered trademarks of Corning Optical Communications.

# Universal Split Base HDPE CVK101035A

UNIVERSAL SPLIT  
BASE HDPE  
CVK101035A

## BENEFITS



Reduces installation time



Versatile design allows base unit to be customized for virtually any application, reducing inventory costs



Reduced cost compared to handhole or aerial terminal and splice points



Provides protection of fiber splices and connectors from dirt, water, flying insects, rodents, floods



Allows easy access to splices, drops, and terminals



Compatible with existing plant



Neutral green color and streamlined profile blends into any environment



Scalable architecture allows growth to match user take-rate. Drops can be added easily without disturbing other subscribers



Mounts on wall, pole, pad (ground), or vault applications

## FEATURES (con't.)

- Available LGX bracket provides mounting capability for Coex modules, cassettes, WDM's, splitters, adapter plates.
- Stake can mount internally or externally and is also reversible.
- Tapered base helps keep pedestal erect and secure with or without stake.
- Square design provides more usable working space than similar size round pedestals.
- Standard 811 outdoor label is available at no charge. Customized labels are also available, and can include logos and text as necessary.
- MADE IN USA.** Meets BABA requirements as well as local and state requirements for all grants.



## DETAILS Refer to ordering guide for pedestal configuration and accessory part numbers.



Split Base



Internal Tunnel for Easy Drop Access



Knockout for bringing drops out



Assembled Pedestal